



---

**Application Procedure**

**750 Foam-Fix** has excellent adhesion to concrete, masonry, brickwork, stone, plaster, wood, fibre cement, metals and several synthetic materials such as styropor, PU-foam, polyester and PVC.

Surfaces should be sound, dry and free from dust and grease. Porous surfaces should be pre-moistened with water.

Shake can vigorously before use. Remove the white protective cap. Screw the applicator nozzle onto the valve. The can must be used upside-down with the valve pointing downwards. By activating the applicator nozzle, the flow of foam can be controlled.

Dispense the foam carefully. Joints and cavities should only be filled by 50% to 70% as foam expands up to twice its original volume. Foam should be applied in beads. Moisturise between layers. Wait for 1 to 2 hours before applying a new layer in very deep holes or joints.

---

**Limits of use**

Read the **danger designation** and **safety box** on the label carefully before dispensing the foam.

- The foam should be used in well-ventilated areas. DO NOT SMOKE.
  - Wear suitable eye protection, gloves and protective clothing.
  - Protect adjacent surfaces from accidental contamination by covering them with paper or plastic sheeting.
  - Remove any fresh (uncured) spilt foam immediately with PU cleaning solvent or acetone.
  - Cured foam can only be removed mechanically.
- 

**Colour**

Yellow

---

**Packaging**

**750 Foam-Fix** (Hand Held application) is supplied in 750ml canisters.

---

**Storage and shelf life**

When stored upright in cool, dry conditions with a maximum temperature of 30°C: maximum 12 months.

---

**Safety**

Consult the **750 Foam-Fix** Material Safety data sheet.

---

**Warning to users**

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. RHODIA SILICONES GUARANTEE THAT THEIR PRODUCTS COMPLY WITH THEIR SALES SPECIFICATIONS.

This information must on no account be used as a substitute for necessary prior tests, which alone can ensure that a product is suitable for a given use.

Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations.

Users are requested to check that they are in possession of the latest version of this document and RHODIA SILICONES are at their disposal to supply any additional information.

---

**Sealants**

*Rhodia Sealants Ltd*  
4 Pomeroy Drive, Oadby, Leicester LE2 5NE, England  
Telephone: 0116 206 3400 - Fax: 0116 206 3414