



# TECHNICAL DATA SHEET

## FIDDES HARD WAX OIL FIDDES EXTERIOR HIGH BUILD WOOD OIL

### Description

A blend of natural oils & waxes offering exceptional durability & resistance for internal natural wood flooring, kitchen worktops (wood) and areas subjected to a high degree of wear.

Produces a quick drying, natural satin / matt water repellent, tread-fast finish that will not peel or flake.

To maintain or renovate, simply wash, buff or re-apply, following the guidelines below.

Suitable for application onto children's toys – EN 71-Toy Safety Test

Resistant to liquids: Tested in accordance with BS 3900 G5

Resistant to wear: Tested in accordance with BS3900 E15

### Preparation

Ensure all surfaces are clean, dry, and free from any previous finish. Sand the substrate with a fine 150 grade sanding paper or 150 grit sanding disk, removing all traces of dust.

### Application guide

Ensure all areas to be coated are extremely well ventilated during and after application. Always test on a small area prior to initial application. No primer required. Maximum 2 coats recommended. Apply at room temperature. Fiddes Hard Wax Oil is formulated for application directly, and does not require thinning.

### First Coat

Stir contents thoroughly before and during use, and apply in a warm, well ventilated room. Apply **THINLY** using a good quality bristle or synthetic brush and lay **EVENLY**, following the direction of the grain. Remove any surplus material immediately with a cloth, carefully checking all areas for any excess application. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight.

### Second Coat

Apply as first coat, **THINLY**, allowing good ventilation. Leave to dry 4-6 hours in warm, dry well ventilated conditions, or preferably overnight.

When the surface area is completely dry, a light buff will further enhance the sheen level.

### Notes:

- 1) Ensure all areas to be coated are extremely well ventilated during and after application has occurred.
- 2) Always test on a small area prior to major application.

Certain dense or oily substrates may only require a single application, and subsequently A blend of natural oils & resins offering a transparent satin finish with exceptional durability and resistance for all external joinery & woodwork.

## **EXTERIOR HIGH BUILD WOOD OIL**

Produces a clear, quick drying, water repellent and weather resistant finish that will not peel or flake. Contains UV Filters and is VOC compliant.

- 1) To maintain/renovate, re-apply following guidelines below. Buff to achieve the desired finish.
- 2) Longer drying periods may occur during application in cold, damp or humid conditions.
- 3) Always apply sparingly and remove any excess product thoroughly.
- 4) Re-Application: To renovate previous application of Fiddes Hard Wax Oil, lightly sand area with 150 grit sandpaper, and re-apply sparingly.



### **Preparation**

Ensure all surfaces are clean, dry, and free from any previous finish. Remove any fungal growth, dirt or moss on old wood prior to application.

Sand the substrate with a medium 120 grade sanding paper or 120 grade sanding disk, removing all traces of dust. Application of exterior high build is the same as interior hard wax oil.

### **Cleaning & Maintenance**

For regular light cleaning, a damp cloth should be applied and resulting clean area left to dry and buffed. Brushing, vacuum cleaning and buffing will also remove any minor blemishes. Periodically, an application of **Fiddes Floor Surface Cleaner** is recommended for areas subject to heavy wear.

Re-application may be necessary in certain areas where soiling or staining is apparent, following the application instructions above.

### **Coverage**

A single application will approximately cover 20-24 square meters per litre, depending on the density of the substrate.

### **Caution**

Flammable: Contains White Spirit

Keep away from sources of ignition: No smoking

Keep out of reach of children

Keep away from food, drink & feeding stuffs

In case of contact with eyes, rinse immediately with plenty of water & seek medical advice

Wear suitable gloves & eye/face protection

Wash out used cloth or store in airtight container: Danger of combustion

### **Storage**

Keep container tightly closed and store in well ventilated area



75 TOWN GREEN STREET  
ROTHLEY  
LEICESTER LE7 7NW  
TEL: 0116 230 1955 – FAX: 0116 230 1944  
[www.constructionchemicals.co.uk](http://www.constructionchemicals.co.uk)